



## Avalanche (POU Water Cooler)

The Avalanche POU system features double float design and a quick connection inlet to enable easy hook-up to filtration equipment or the water supply. Still boasting its excellent chilling capacity and robust build, this countertop POU is top-of-the-line.

### Avalanche: Hot & Cold



Avalanche faucet



LED display



Carrying handle

ITEM		SPECIFICATIONS
Power rating		Single phase 100-115VAC 60Hz
Standard current	100-115VAC	H&C: 6.2A
Power	Cold	74W
Consumption	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Capacity	3.5L (0.9 gal)
Hot	Temp control	Bimetal 75-92°C (167-197.6°F )
	Capacity	4.5L (1.2 gal)
Refrigerant charge		28.4g (1.0 oz)
Net weight		Hot & Cold: 11.3kg (24.8 lb)
Product dimensions		330(W) X 368(D) X 419(H)mm 13.0"(W) X 14.5"(D) X 16.5"(H)
Product boxed dimensions		360(W) x 375(D) x 447(H)mm 14.2"(W) x 14.8"(D) x 17.6"(H)
Loading quantity		20' Container: 450 Units 40' Container: 960 Units
Certifications		C-UL-US, CE, CB

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at [cmsales@crystalcoolers.com](mailto:cmsales@crystalcoolers.com)